



ユニット 呼び番号	軸径 (mm)	寸法 (mm)										呼び番号	軸受		軸受箱 呼び番号	質量 (kg)
		L	A	J	H	H ₂	H ₃	N	L ₁	B	S		基本定格荷重			
													Cr(kN)	Cor(kN)		
UCPA201	12	76	40	52	30.2	62	13	M10×1.5	27	31	12.7	UC201	12.8	6.65	PA204	0.64
UCPA201L2												UC201L2				
UCPA202	15	76	40	52	30.2	62	13	M10×1.5	27	31	12.7	UC202	12.8	6.65	PA204	0.62
UCPA202L2												UC202L2				
UCPA203	17	76	40	52	30.2	62	13	M10×1.5	27	31	12.7	UC203	12.8	6.65	PA204	0.61
UCPA203L2												UC203L2				
UCPA204	20	76	40	52	30.2	62	13	M10×1.5	27	31	12.7	UC204	12.8	6.65	PA204	0.59
UCPA204L2												UC204L2				
UCPA205	25	84	45	56	36.5	72	13	M10×1.5	30	34.1	14.3	UC205	14.0	7.85	PA205	0.83
UCPA205L2												UC205L2				
UCPA206	30	94	50	66	42.9	84	18	M14×2	36	38.1	15.9	UC206	19.5	11.3	PA206	1.2
UCPA206L3												UC206L3				
UCPA207	35	110	55	80	47.6	95	20	M14×2	41	42.9	17.5	UC207	25.7	15.4	PA207	1.7
UCPA207L3												UC207L3				
UCPA208	40	116	58	84	49.2	100	20	M14×2	41	49.2	19	UC208	29.1	17.8	PA208	2
UCPA208L3												UC208L3				
UCPA209	45	120	60	90	54.2	108	25	M14×2	42	49.2	19	UC209	34.1	21.3	PA209	2.2
UCPA209L3												UC209L3				
UCPA210	50	130	64	94	57.2	113	25	M16×2	47	51.6	19	UC210	35.1	23.3	PA210	2.8
UCPA210L3												UC210L3				

備考

- 軸受の形状及び寸法はUC2に示す。
- グリースニップルは、1/4-28UNFである。